



Galaxy GRS



GALAXY GBS 10 SERIES

GBS 10/650 HELI

REPACKING MANUAL

GALAXY GRS s.r.o. © 2020

1 REPACKING MANUAL

This is an additional manual for repacking of a special version HELI.

- 1) Fold the parachute as described in the regular 10/650 manual.



- 2) Prepare the red inside parachute container





- 3) Fold the canopy in the shape of “harmonica” into red fabric inside container, starting from the top of the canopy.



- 4) Whole canopy must be inside including approximately 10-20 cm of parachute lines. Cover all 4 lids over the canopy. Insert the 10 mm fold with lines through the white loop (attached on the bottom lid). This fold is securing the position of the canopy inside the red container. This fold is released by a kinetic energy of the canopy after system activation.



5) Fold the rest of lines into orange fabric cover





- 6) Put the red fabric container together with the orange container with lines.



- 7) Insert 3x pyroactuators into the bottom of canister with respecting **SAFETY RULES!**
- 8) Insert the piston over the 3 pyroactuators, respect the position of the groove on the piston, which must match with the shape of the bottom of canister. Position the belt into the groove on the canister edge.





- 9) Put the yellow cap over the parachute canister.
- 10) Use the additional 2m white belt. Make a loop under the rotor head and attach it on the fuselage, make it easy to detach.
- 11) Connect the opposite part with the parachute belt and rest of 2m belt attach close to the parachute canister. Make it easy to detach.
- 12) Incline the whole canister approx 15° up as on the picture.
- 13) Immediate engine stop is required, rotor must be without torque immediately and stopped within 1 sec.



